

TECHNICAL DATA SHEET

PASTE FAST-CUT COMPOUND

(NOBEL COMPOUND N 100)

PRODUCT DESCRIPTION

Nobel N100 is a high-performance water-based fast-cut compound used for the removal of P1500 or finer (sanding) scratches. It is a silicone and wax-free product that delivers a high gloss finish. It is used with a white sponge or a wool pad. It can also be used for polish by hand.



Key benefits

speed	Fast removal of scratches
Finish	High gloss finishes
Easy to use	Simple dry use with no water addition and easy removal of the product spatter from adjacent panels
Permanent results	no reappearance of sanding marks

product features

contains no fillers so scratch marks won't re-appear

Silicone free


technical information

Product group	Silicone and wax free
Viscosity	44-55 Poise
Density	1.05 -1.12kg/L
Shape	liquid form
Color	White
Package	250gm

034707063 

11723 

728697904 



شارع الغازات الكيلو 23 طريق القاهرة
الاسكندرية الصحراوي مرغم .العامرية 

Technical Information and direction of use

Technical Information

Cut	8
Gloss	7

Application

		Direction of use	
Maximum abrasion		P1500 or finer	
Polishing tool		Heavy cut foam pad	
Rotational Speed		1200-1800 r.p.m	
Polishing machine		A rotary or an orbital polishing machine	Apply a small quantity of the product to the pad. Start the machine at medium speed and gradually increase the speed using light pressure.


General notes

- ✓ Apply NOBEL N 105 out of the direct sunlight.
- ✓ Apply NOBEL N 105 onto the cool surface.
- ✓ Apply NOBEL N 105 onto Clean surface.
- ✓ If surface is dry, a little water onto the surface can prevent dust formation.
- ✓ Reduce pressure 2-3 second before the end of rubbing process to get high gloss
- ✓ Remove residue using premium micro fiber cloth.


Machine Application




Soak the compounding foam in water.




Attach the pad to the polishing machine spin off the excess water.



Shake or mix the compound well , then apply to the pad



Spread at 1000 rpm and compound at 1500 - 1800rpm with light pressure Apply more water if necessary.




Wipe clean with Finishing Cloth.


Hand Application




Soak the hand compounding foam or the microfiber cloth in water.



Shake or mix the compound well , then apply to microfiber cloth or surface.




Rub the product on the surface in back and forth motion



Apply water if necessary. Wipe clean with microfiber cloth.

Storage



Keep away from frost.
Store between 15°C and 35°C.
Store in well-ventilated area.

Health and Safety

1. For full Health and Safety information refer to the Material Safety Data Sheet (MSDS).
2. Observe the precautionary notices displayed on the container.
3. Goggles and gloves should be worn while using these products.
4. Good ventilation must be provided in the working environment.