

TECHNICAL DATA SHEET

WOOD STAIN

(NOBEL STAIN)

PRODUCT DISCRITION

Nobel STAIN IS AHIGH QUALITY STAIN, FORMULATED FROM HIGH-QUALITY DYES WHICH CAN BE DILUTED WITH WATER AND THINNER .IT IS VERY EFFECTIVE IN COLORING FURNITURE AND WOOD WORKS AS IT EMPHASIZES THE NATURAL BEAUTY OF WOOD.

Uses

It is specially designed for coloring of wooden surfaces before applying nitrocellulose, synthetic, polyester and polyurethane transparent finishes when natural look of wood is desired.

It penetrates bare wood, provides fast drying and good light fastness and can be used for coloring of wooden surfaces indoor. The product is offered in a pallet of shades according to Nobel Wood Stains color chart.



product features

SOLVENT BORNE PRODUCT
GOOD UV RESISTANCE
REGULAR PENETRATION ON SUBSTRATE

technical information

Appearance	COLORED LIQUID
SPECIFIC GRAVITY	0.88-0.91KG/L
FLASH POINT	20°C
COVERAGE/COAT	10 – 12 M ² DEPENDING ON THE COLOR STRENGTH REQUIRED

034707063 

11723 

728697904 


شارع الغازات الكيلو 23 طريق القاهره
الاسكندريه الصحراوي مرغم .العامة 

Substrate and surface preparation

Surface must be clean and free from oil grease dirt limescale and any other foreign contaminant
Sandpaper is applied in the direction of the wood grain and it is taken into account to wipe the dust
Close the pores by repeated application of sealer of Nobel product

Application

Nobel Wood Stain
Nobel super NC thinner/ or Water/ or Alcohol



Mixing ratio by weight:

Mixing ratio: Mix 1 part of Nobel wood stain with 2 Parts of Nobel super NC Thinner or Alcohol to get the same color in the swatch

Drying time



Apply several coats by brush or by lint-free cotton to get the desired shade.



Dry to overcoat: 15-20 min/25°C

Theoretical coverage

1. 8 – 10 m²/kg per coat
2. Practical coverage depends on several factors including shape, roughness and porosity of the object to be painted, spraying equipment used, application methods, application conditions, film thickness, etc.
3. For best results, it is always recommended to test the products on scrap pieces of wood before startpaint job

Shelf life

3 years from production date stored in original packaging at normal conditions. And away from direct sunlight and heat

Health and Safety

1. For full Health and Safety information please refer to the Material Safety Data Sheet.
2. Observe the precautionary notices displayed on the container.
3. Good ventilation must be provided in the working environment

034707063 

11723 

728697904 

شارع الغازات الكيلو 23 طريق القاهرة
الاسكندرية الصحراوي مرغم. العامرية 